In re WONG et al.
10/006,342
Response to Office Action dated July 26, 2005
Page 4 of 15

IN THE CLAIMS

Claims 1-11: CANCELED

12. (Previously Presented) An electronic device comprising:

a housing that contains one or more components of the electronic device;

a display assembly including a screen for displaying output, the screen being provided on a

front panel of the housing;

a bezel feature coupled to the display assembly to at least partially circumvent the display

assembly, wherein the bezel feature is rotatable about a rotation axis;

a lid provided as part of the bezel feature, wherein the lid is coupled to the bezel feature to

move between an open position and a closed position, wherein in the closed position,

the lid covers at least a portion of the display assembly, and in the open position, the

lid is at least partially upright to provide access to the screen of the display assembly;

an interface for the bezel feature; and

a processor coupled to the bezel feature via the interface to detect any one of the plurality of

positions of the bezel feature, and to perform one or more operations based on the

detected position of the bezel feature.

Claims 13-14: CANCELED

In re WONG et al.
10/006,342
Response to Office Action dated July 26, 2005
Page 5 of 15

15. (Previously Presented) The electronic device of claim 12, wherein the bezel feature is

actuatable to cause an input to be entered into the electronic device, the input corresponding

to a rotation of the bezel feature.

Claims 16-18: CANCELED

19.   (Previously Presented) The electronic device of claim 12, wherein the display

assembly is contact-sensitive and formed at least partially by a contact-sensitive material,

and wherein the bezel feature is also at least partially formed by the contact-sensitive

material so as to be at least partially integrated with the display assembly.

In re WONG et al.
10/006,342
Response to Office Action dated July 26, 2005
Page 6 of 15

20.   (Previously Presented) The electronic device of claim 12, wherein a diameter length of the bezel feature is greater than a length of the display assembly.

21. (Original) The electronic device of claim 12, wherein a diameter length of the bezel feature is at least 50% of a length of the electronic device.

22. (Original) The electronic device of claim 12, wherein a diameter length of the bezel feature is at least 90% of a length of the electronic device.

23. CANCELED

24. (Currently Amended) The electronic device of claim 12, wherein the lid is formed from material that is transparent so that the screen of the display assembly is viewable when the bezel feature is in the closed position.   .

25. (Previously Presented) The electronic device of claim 12, wherein the bezel feature forms a perimeter portion of the housing.

26. (Previously Presented) The electronic device of claim 12, wherein the processor is configured to detect a rotation of the bezel feature via the interface, and wherein the rotation of the bezel feature causes the processor to launch an application.

27. (Previously Presented) The electronic device of claim 12, wherein the processor is configured to detect a rotation of the bezel feature via the interface, and wherein rotation of the bezel feature causes the processor to present one or more items on the screen of the display assembly for selection.

In re WONG et al.
10/006,342
Response to Office Action dated July 26, 2005
Page 7 of 15

28. (Currently Amended) The electronic device of claim 26, wherein the processor is

configured to perform one or more operations based on a radial change in position of a

reference pointpointer of the bezel feature as a result of the rotation.

Claims 29-34: CANCEL

35. (Currently Amended) An electronic device comprising:

a housing that contains one or more components of the electronic device;

a display assembly including a screen provided on a front panel of the housing, wherein

      the display assembly is contact-sensitive;

a processor configured to:

      display a bezel feature on the display assembly, the displayed bezel feature

          including a circumferential track;

      detect a continuous contact with the display assembly resulting in a reference

          point pointer of the bezel feature being moved from a starting point on the

          track to a finishing point on the track, wherein at least one of the starting

          point and finishing point is on a surface portion of the screen

          corresponding to where the bezel feature is displayed;

      determine an input based on the continuous contact, wherein the input is based on

          a position of at least one of the starting point and the finishing point; and

In re WONG et al.
10/006,342
Response to Office Action dated July 26, 2005
Page 8 of 15

perform an operation based on the input.

36. (Previously Presented) The electronic device of claim 35, wherein the processor is
configured to display the bezel feature on a perimeter of the screen of the display
assembly.

37. (Previously Presented). The electronic device of claim 35, wherein in response to the
continuous contact, the processor is configured to present one or more items on the screen
of the display assembly for selection.

38. (Currently Amended) The electronic device of claim 35, wherein in response to the
continuous contact, the processor is configured to perform one or more operations, the
one or more operations being selected based on the continuous contact being interpreted
as a radial change in position of a ~~reference point~~graphic feature on the track. ~~on the
bezel feature as a result of the continuous contact.~~

39. (Previously Presented) The electronic device of claim 35, wherein the processor is
configured to perform one or more operations based on one or more of a duration of the
continuous contact.

40. CANCELED

41.   (Currently Amended) An electronic device comprising:
a housing having a front panel;
a display provided on the front panel;
a processor housed within the housing; and

In re WONG et al.
10/006,342
Response to Office Action dated July 26, 2005
Page 9 of 15

a bezel feature provided on the front panel, wherein the bezel feature is a hardware

component that interfaces with the processor, and wherein the bezel feature

includes a track provided on the front panel and is formed by a contact-sensitive

material that provides a surface capable of detecting contact from a user at one or

more positions on the track, wherein the contact indicates ~~on which a pointer may~~

~~be dragged to indicate~~ an input;

and wherein the processor is configured to perform an operation corresponding to a

selection of an application based on an input received through operation of the

bezel feature.

42. (Currently Amended) The electronic device of claim 41, wherein the bezel feature

is responsive to a drag of a pointer from a first position of the ~~bezel feature~~track to a

second position of the ~~bezel feature~~track.

43. (Previously Presented) The electronic device of claim 41, wherein the processor is

also configured to use input provided by the bezel feature to set a digital clock.

44. (Previously Presented) The electronic device of claim 41, wherein the processor is

also configured to use input provided by the bezel feature to select an alphanumeric

character.

45. (Previously Presented) The electronic device of claim 41, wherein the processor is

configured to affect a content appearing on the display while performing the operation.

46. (Previously Presented) The electronic device of claim 41, wherein the bezel

feature includes a dimension that is at least 50% of a greatest dimension of the housing.

47. (Previously Presented) The electronic device of claim 41, wherein the bezel

feature includes a dimension that is at least 80% of a greatest dimension of the housing.

In re WONG et al.
10/006,342
Response to Office Action dated July 26, 2005
Page 10 of 15

48.   (Previously Presented) The electronic device of claim 41, wherein the processor is

configured to (i) detect a user moving the pointer an arc length from a reference, (ii)

interpret a position of the pointer from the reference as an input.

49.   (New) The electronic device of claim 41, wherein at least one of the processor or

the bezel feature is configured to provide a tactile feedback in response to operation of the

bezel feature.